

POWER PACKS



BHP350 • BHP250 • BHP170
 Serious Power for
 Maximum Performance



Technical Specifications

GENERAL	BHP170	BHP250	BHP350
Weight	4500-5500 lbs	8500 lbs	7000-10000 lbs
Length	42"	48"	Custom
Width	96"	114"	Width of Excavator
Engine	Cummins - QSB 4.5 John Deere - 4045	CAT C-7 John Deere 6068	Cummins QSL 8.9
Number of Cylinders	4	6	6
Gross Power	Cummins 170hp@2500 RPM John Deere 140hp@2400 RPM	CAT - 250hp@2200 RPM John Deere 250hp@2500 RPM	350hp@1800 RPM
Fuel Capacity	*Optional	100 US Gallons	85 US Gallons
Fuel consumption	6 to 8 gph	8 to 11 gph	10 to 12 GPH
Hydraulic System	6,000 psi	6,000 psi	6,000 psi
High Flow	65 gpm	105 gpm	120 gpm

BHP NEW GENERATION POWER PACK

The perfect combination of brains and brawn. The BHP is controlled by a true POWERMANAGEMENT® MICROCONTROLLER. This feature gives all of the available power to the brush cutter. There is no power loss due to accessories. The performance of the BHP and brush cutter is maximized at all times taking full advantage of the maximum horsepower of the Power Pack.

The microcontroller manages the head flow, engine and hydraulic needs in real time. This system captures the full potential of grinding power. Performance is far superior to Power Packs without this feature.

ALL Power Packs include Fecon Power Management®



FEATURES

- Equipped with Fecon Power Management®
- Dramatically improves engine response/recovery
- Sustained peak grinding power
- Reduced fuel consumption
- Optimized operator feedback
- Limited stalling
- Quicker recovery
- Maximized productivity

APPLICATIONS

- R.O.W.
- Land Clearing
- Forestry Applications
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Agricultural Preparation and Land Development
- Invasive Species - Beetle Kill and Noxious Weeds.
- Wild Fire Urban Interface Mechanical Fuel Treatments.
- Mulch Brush, Branches, Slash, Standing and Fallen Trees, Root Balls, and Stumps

* Specifications subject to change without notice

- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal).
- Safety Is The Responsibility Of The Operator.
- Always insure that your carrier manufacturers safety features, including Falling Object Protection and Roll-Over Protection, meet your job safety requirements.
- LEXAN® is a registered trademark of General Electric Company.

3/08



3460 Grant Drive
Lebanon, OH 45036
www.fecon.com
E-Mail: sales@fecon.com



Phone: 513.696.4430
Fax: 513.696.4431
Toll Free: 800.528.3113