

# FECON<sup>®</sup>

## 8-12 TON EXCAVATOR CAB GUARD

- Separate upper & lower 1/2" polycarbonate windows attached to a painted steel frame
- Hinged polycarbonate allows for emergency egress for front exit cabs and easy cleaning (4" spacing)
- Pivoting lower sections allows better fitment across cab sizes
- Universal mounting locations allows the guard to fit most 8-12t excavators without drilling or welding
- Less than 30 minutes to install
- Weight: Approx 100lbs



### SPECS AND DIMENSIONS:

Frame outside width:	39.25"
Frame overall width (w/ handle):	42.5"
Frame overall height:	65.875"
Bottom hinge angle:	35 Deg
Upper frame outside height:	45.375"
Upper frame outside width:	39.25"
Upper frame cutout height:	41"
Upper frame cutout width:	33.875"
Lower frame outside height:	22.375"
Lower frame outside width:	39"
Lower frame cutout height:	20"
Lower frame cutout width:	33.875"

# FECON<sup>®</sup>

fecon.com • sales@fecon.com  
800 528 3113 • +1 513 696 4430



- Operators cab must be protected with both properly maintained 1/2" LEXAN<sup>®</sup> Glass (or equal) and Falling Object Protection.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
  - Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options. • Safety Is The Responsibility Of The Operator. • Pictures may contain optional accessories
  - Specifications subject to change without notice. • Photographs may have been altered for marketing purposes.